



FLOOR STANDINGS **NEW** // Dimensions



OUTDOOR UNITS **NEW** // Dimensions



R32/R410A
INVERTER FLOOR STANDING
AIR CONDITIONERS 2023



Authorized Distributor:
Panaserv Nigeria Limited
Showrooms & Service Centers

- ▶ **Lekki**
30B, ADMIRALTY WAY, LEKKI PHASE1, LEKKI, LAGOS
Tel :08141306383
- ▶ **Abuja**
SUITE A-11, AL-FAISALMAS PLAZA, AREA 11, GARKI, ABUJA
Tel :08141306373
- ▶ **Enugu**
86, OGUI ROAD, ASTA, ENUGU
Tel :08142095421
- ▶ **Victoria Island**
247B, MURI OKUNOLA STREET, VICTORIA ISLAND, LAGOS
Tel :08108371888
- ▶ **Ikeja**
49, ALLEN AVENUE, IKEJA, LAGOS
Tel :08065808181
- ▶ **Kano**
48, BOMPAI ROAD, KANO
Tel :08063284539
- ▶ **Port Harcourt**
20, TRANS AMADI INDUSTRIAL LAYOUT, PHOR HARCOURT
Tel :07033088474



A Better Life, A Better World

Product Lineup

- All new models equipped with nanoe™ X Generator Mark 2 as standard
- Little installation work required, easy to clean
- Adjustable airflow direction provides a comfortable space for all

Type	Btu	20,500	24,600	34,100	42,700	47,750
Refrigerant		R32	R32	R410A	R410A	R410A
Floor standing		S-21PB3H5	S-24PB3H5			
Floor standing				S-34PB3H5	S-43PB3H5	S-48PB3H5
Outdoor		U-21PRB1H5	U-24PRB1H5	U-34PSB3H5	U-43PSB3H5	U-48PSB3H5

FLOOR STANDING

- Stylish design & powerful air flow
- The control panel/remote controller have nanoe™ X displays
- Compact 34,100 Btu ODU (210 mm shorter/27 kg lighter than current model)




Capacity (Btu/h)		20,500	24,600	34,100	42,700	47,750
Power Source	V/Phase Hz	220/230V, 10 Phase - 50Hz				
Indoor		S-21PB3H5	S-24PB3H5	S-34PB3H5	S-43PB3H5	S-48PB3H5
Outdoor		U-21PRB1H5	U-24PRB1H5	U-34PSB3H5	U-43PSB3H5	U-48PSB3H5
Cooling Capacity: Rated (Min-Max)	kW	6.05 (1.00-6.60)	7.25 (1.00-7.50)	10.00 (1.20-10.30)	12.53 (2.00-13.50)	14.00 (2.00-14.60)
	Btu/h	20,500 (3,410-22,500)	24,600 (3,410-25,570)	34,100 (4,090-35,120)	42,700 (6,820-46,030)	47,750 (6,820-49,780)
Current: Rated (Max)	A	8.00 (11.2)	11.2 (13.7)	15.1 (16.9)	20.3 (26.9)	25.6 (28.1)
Cooling Power Input: Rated (Min-Max)	kW	1.80 (0.21-2.30)	2.55 (0.21-2.80)	3.45 (0.30-3.60)	4.47 (0.80-5.00)	5.60 (0.80-5.70)
	W/W	3.36	2.84	2.89	2.80	2.50
Cooling Rated COP/EER	Btu/hW	11.3	9.64	9.88	9.55	8.52
Indoor Unit						
Cooling Air Volume	m³/min	15.5	15.5	32.0	32.0	32.0
	cfm	547	547	1,130	1,130	1,130
Sound Pressure Level (Hi/Lo)	dB (A)	45 / 31	45 / 33	53 / 44	53 / 44	53 / 44
Sound Power Level (Hi/Lo)	dB	58 / 44	58 / 46	66 / 57	66 / 57	66 / 57
Dimension	Indoor (HxWxD) mm	1,680 x 500 x 318	1,680 x 500 x 318	1,880 x 600 x 357	1,880 x 600 x 357	1,880 x 600 x 357
Net Weight	Indoor kg	29	29.5	45.0	45.0	45.0
Outdoor						
Sound Pressure Level	dB (A)	53	54	54	55	56
Sound Power Level	dB	66	67	67	68	69
Dimension Outdoor (HxWxD)	mm	626 x 825 x 320	626 x 825 x 320	786 x 900 x 320	996 x 940 x 340	996 x 940 x 340
Net Weight	kg	35.0	36.0	45.0	74.0	74.0
Piping Connection	Gas Pipe mm (inch)	12.70 (1/2)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)
	Liquid Pipe mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	9.52 (3/8)	9.52 (3/8)
Pipe Length	Min-Max m	3 - 40	3 - 40	7.5 - 50	7.5 - 50	7.5 - 50
Elevation Difference (Outdoor unit upper)	m	20	20	20	30	30
Maximum Chargeless Length Max	m	15	15	20	20	20
Additional Gas	g/m	10	10	40	50	50
Operation Range, Outdoor	Min-Max °C	18-43	18-43	18-43	18-43	18-43

* Specifications are subject to change without notice. Please refer to technical documents for more details.
* The sound pressure level is measured in accordance with JIS C 9 612 and JIS B 8616.

NEW nanoe™ X Bringing Nature's Balance Indoors

The well-being benefits of nature are well known but do you know the power of hydroxyl radicals?

Abundant in nature, hydroxyl radicals (also known as OH radicals) inhibit pollutants, viruses and bacteria to clean and deodorise. nanoe™ X technology can bring these incredible benefits indoors.



S-21/24 PB3H5

S-34/43/48 PB3H5

7 Effects of nanoe™ X : Creating Cleaner Environments

nanoe™ X inhibits 5 types of pollutants, deodorises and moisturises thanks to the action of hydroxyl radicals contained in water.

Deodorises



Odours

Inhibits 5 types of pollutants



Bacteria & viruses



Mould



Allergens



Pollen



Hazardous substances

Moisturises



Skin & Hair




nanoe™ X Effectiveness Proven in Large Space

Access to the evidence page of nanoe™ X effect

Clean airflow direction control with remote controller

Easily swing the louvre at the touch of a button.



Other Functions

Random auto restart

During a power failure, when power is restored, it automatically restarts operating in the same mode as just before power was lost.

Auto fan mode

When the auto fan mode is set, the indoor unit of the air conditioner automatically adjusts the suitable fan speed according to factors such as load.

12-hour On/Off delay setting timer

Pressing the timer button on the remote control lets you set operation start/stop time within 12 hours of the current time.



* The images above show the remote controller screen display.