

Panasonic[®]

Product Specification Sheet

IP Video Intercom System – Power Distributor

Model No. VL-PC3800BX



1. Basic information

- Dimension: Approx. 95mm x 200mm x 30mm
- Colour: Dark Grey
- External material: ABS
- Installation: DIN-Rail Mounting

2. Features

- UPLINK port is for data transfer
- Provide 3 modes: 10M / 100M / Normal (Power disabled)

3. Specifications

Network Parameters	
Wiring	UTP (Cat 5e or higher)
Device Interfaces	
Network Interface	RJ45, 10BASE-T/100BASE-TX (Auto MDI/MDI-X)
General	
Power Source	Power supply unit (Sold separately)
Operating Voltage	18 to 27VDC
Current Rating	DC 12V, 670mA; DC 27V, 300mA
Power Consumption	Standby: 0.5W
Installation Method	DIN-Rail Mounting
Colour	Dark Grey
Dimensions (H x W x D)	Approx. 95mm x 200mm x 30mm
Operating Temperature	-25°C to +70°C
Storage Temperature	-40°C to +70°C
Operating Humidity	Up to 90% (non-condensing)
IP rating (Ingress Protection)	IP30
IK rating (Impact Protection)	—
External Material	ABS
Weight	Without package: 250g With package: 325g

Copyright © 2024 Panasonic. All rights reserved.

- Actual products may vary slightly from photographs.
- Specifications & features are subject to change without notice.

DISTRIBUTED BY:

Panasonic[®]