

FLOOR STANDING

- Stylish design & powerful airflow
- The control panel/remote controller have nanoe™ X displays
- Compact 34,100 Btu ODU (210 mm shorter/27 kg lighter than current model)



S-21PB3H5/
S-24PB3H5

(S-21/24PB3H5
(standard)



S-34PB3H5/
S-43PB3H5/
S-48PB3H5

(S-34/43/48PB3H5
(standard)



Capacity [Btu/h]		20,500	24,600	34,100	42,700	47,750
Power Source	V/Phase Hz	220/230V, 1Ø Phase - 50Hz				
Indoor		S-21PB3H5	S-24PB3H5	S-34PB3H5	S-43PB3H5	S-48PB3H5
Outdoor		U-21PRB1H5	U-24PRB1H5	U-34PSB3H5	U-43PSB3H5	U-48PSB3H5
Cooling Capacity: Rated (Min-Max)	kW	6.05 [1.00-6.60]	7.25 [1.00-7.50]	10.00 [1.20-10.30]	12.53 [2.00-13.50]	14.00 [2.00-14.60]
	Btu/h	20,500 [3,410-22,500]	24,600 [3,410-25,570]	34,100 [4,090-35,120]	42,700 [6,820-46,030]	47,750 [6,820-49,780]
Current: Rated (Max)	A	8.00 [11.2]	11.2 [13.7]	15.1 [16.9]	20.3 [26.9]	25.6 [28.1]
Cooling Power Input: Rated (Min-Max)	kW	1.80 [0.21-2.30]	2.55 [0.21-2.80]	3.45 [0.30-3.60]	4.47 [0.80-5.00]	5.60 [0.80-5.70]
Cooling Rated COP/EER	W/W	3.36	2.84	2.89	2.80	2.50
	Btu/hW	11.3	9.64	9.88	9.55	8.52
Indoor Unit						
Cooling Air Volume	m³/min	15.5	15.5	32.0	32.0	32.0
	cfm	547	547	1,130	1,130	1,130
Sound Pressure Level (Hi/Lo)	dB (A)	45 / 31	45 / 33	53 / 44	53 / 44	53 / 44
Sound Power Level (Hi/Lo)	dB	58 / 44	58 / 46	66 / 57	66 / 57	66 / 57
Dimension	Indoor [HxWxD] mm	1,680 x 500 x 318	1,680 x 500 x 318	1,880 x 600 x 357	1,880 x 600 x 357	1,880 x 600 x 357
Net Weight	Indoor kg	29	29.5	45.0	45.0	45.0
Outdoor						
Sound Pressure Level	dB (A)	53	54	54	55	56
Sound Power Level	dB	66	67	67	68	69
Dimension Outdoor (HxWxD)	mm	626 x 825 x 320	626 x 825 x 320	786 x 900 x 320	996 x 940 x 340	996 x 940 x 340
Net Weight	kg	35.0	36.0	45.0	74.0	74.0
Piping Connection	Gas Pipe mm (inch)	12.70 (4/8)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)
	Liquid Pipe mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	9.52 (3/8)	9.52 (3/8)
Pipe Length	Min-Max m	3 - 40	3 - 40	7.5 - 50	7.5 - 50	7.5 - 50
Elevation Difference (Outdoor unit upper)	m	20	20	20	30	30
Maximum Chargeless Length Max	m	15	15	20	20	20
Additional Gas	g/m	10	10	40	50	50
Operation Range, Outdoor	Min-Max °C	18-43	18-43	18-43	18-43	18-43

* Specifications are subject to change without notice. Please refer to technical documents for more details.

* The sound pressure level is measured in accordance with JIS C 9 612 and JIS B 8616.