


ANYWHERE, ANYTIME, QUALITY INDOOR AIR



Hotel



Office



Car



Bedroom

SPECIFICATIONS

Model	Estimated Applicable Volume	Air Volume	Noise	Power Consumption	Voltage	Power Cord	Dimensions (Height x Top x Base)	Weight
F-GPT10M	3m ³	1.1L/s	34dB	3.5W	DC 5V (Adaptor 1.5A)	1.5m USB-A to USB-C	170 x 90 x 66mm	0.4kg

Eliminates 99% bacteria in 3m³ space in 2 hours [Test organization] Guangzhou Institute of Microbiology Research [Report no. KJ20203596-2]

Condition for generating nanoe™X

- Room temperature : about 5°C ~ 40°C (dew point temperature more than 2°C)

- Relative humidity : about 30% ~ 85%

nanoe™X is generated using the air in the room, and its amount is subject to the temperature and humidity.

EFFECTIVENESS OF nanoe™X

DEODORISES



Odours

INHIBITS 5 TYPES OF POLLUTANTS



Bacteria & Viruses



Mould



Allergens



Pollen



Hazardous Substances

MOISTURISES



Skin & Hair

For further details and validation data, please refer to the following website:

www.panasonic.com.au/nanoe



Please read the Installation Instructions carefully before installing the unit, and the Operating Instructions before using it. Specifications are subject to change without prior notice. The contents of this catalogue are accurate as of October 2021. Due to printing considerations, the actual colours may vary slightly from those shown. All graphics are provided merely for the purpose of illustrating a point.

21VEN1101PN

Panasonic Australia Pty. Limited

1 Innovation Road,
Macquarie Park,
NSW 2113
ACN 001 592 187
ABN 83 001 592 187
Website : aircon.panasonic.com.au

Panasonic

AIR CONDITIONING